

Class O Perimeter Foil Tape

Rolls of 40mm Wide x 45Lm Long 30 Microns Thick

A Robust self adhesive Foil Tape used to seal cut edges of Perimeter or Cut Panels to preserve the Class 'O' Spread of Flame requirement for Raised Access Floors. Aluminium foil tape is produced with an aggressive acrylic adhesive that provides a wide range of application temperatures and are Class 'O' fire rated for use in insulation, raised flooring, air conditioning and ducting applications.

A Class O performance is specified where it is necessary to maintain the flame resistance to cut the panel edges and to prevent moisture ingress:

- gives a Class 1 result when tested in accordance with BS476: Part 7: 1997
- has a fire propagation index (I) of not greater than 12 and a sub-index (i1) of not greater than 6 when tested in accordance with BS476: Part 6: 1989

The definitions for Class O products are given in the following Documents.

- Appendix A (paragraph 12) of Approved Document B, Fire Safety, to the Building Regulations England and Wales 1991.
- Appendix to Part D (paragraph 6a), Structural Fire Precautions, of the Technical Standards for compliance with the Building Standards (Scotland) Regulations 1990.
- Section 2 (paragraph 2.4) of Technical Booklet E, Fire Safety, to the Building Regulations (Northern Ireland) 1994.

Carrier:	30µ soft tempered bright aluminium foil
Adhesive:	WM 1070 pure acrylic permanent
Release liner:	65gsm siliconised honey glassine
Tape Thickness:	0.060 mm (without liner)
Carrier Thickness:	0.030 mm
Adhesive colour:	Clear
Roll width:	40mm
Roll length:	45Lm



Other Ancillaries



Yellow Sealer
 Red Sealer
 XP 2788 Adhesive
 Permaflor1 Adhesive
 Class O Foil Tape
 Class O Perimeter Gasket Tape
 Sleeved M6 x 40mm Nail In Anchor Fixing
 Masonry Drill Bit 6.5mm
 M6 x 45mm Taptite Machine Screw
 BAG600BX Floor Grille
 Support Strings