


SILENT LIGHT RANGE



SILENT Y

ACOUSTIC PENDANT LUMINAIRE

Suspended acoustic Y shape pendant ideal for reducing noise in meeting spaces and open plan areas.



Code	Type	Length	Width	Height	Accepts Luminaire
AC/SY/0600/200/**/AL	Accepts light	600x600x600	75	200	Polaris 50 Y - 600mm
AC/SY/0875/200/**/AL	Accepts light	875x875x875	75	200	Polaris 50 Y - 875mm
AC/SY/1145/200/**/AL	Accepts light	1145x1145x1145	75	200	Polaris 50 Y - 1145mm
AC/SY/1430/200/**/AL	Accepts light	1430x1430x1430	75	200	Polaris 50 Y - 1430mm
AC/SY/0600/300/**/AL	Accepts light	600x600x600	75	300	Polaris 50 Y - 600mm
AC/SY/0875/300/**/AL	Accepts light	875x875x875	75	300	Polaris 50 Y - 875mm
AC/SY/1145/300/**/AL	Accepts light	1145x1145x1145	75	300	Polaris 50 Y - 1145mm
AC/SY/1430/300/**/AL	Accepts light	1430x1430x1430	75	300	Polaris 50 Y - 1430mm
AC/SY/0600/200/**/PB	Plain baffle	600x600x600	75	200	N/A
AC/SY/0875/200/**/PB	Plain baffle	875x875x875	75	200	N/A
AC/SY/1145/200/**/PB	Plain baffle	1145x1145x1145	75	200	N/A
AC/SY/1430/200/**/PB	Plain baffle	1430x1430x1430	75	200	N/A
AC/SY/0600/300/**/PB	Plain baffle	600x600x600	75	300	N/A
AC/SY/0875/300/**/PB	Plain baffle	875x875x875	75	300	N/A
AC/SY/1145/300/**/PB	Plain baffle	1145x1145x1145	75	300	N/A
AC/SY/1430/300/**/PB	Plain baffle	1430x1430x1430	75	300	N/A

• ** Please specify colour

• Range of lights available from the Synergy Polaris Y range - to be specified separately



SILENT LIGHT RANGE

SILENT ECLIPSE

ACOUSTIC PENDANT LUMINAIRE

Finish Options



Material Details

Synergy is proud to use recycled PET (Polyethylene Terephthalate) in our acoustic lighting. PET is a form of polyester, which is usually used in plastic bottles for drinks, detergent, salad dressings and the like.

Composition – 100% PET (Polyethylene Terephthalate) with a 60% recycled content

Environmental - Acoustic material has a 60% recycled content, and is recyclable.

Standards – Fire specification - EN13501-1 Class B-s1,d0

Acoustic performance – EN ISO 354:2003

Non-hazardous – no formaldehyde binders are used in the manufacturing process.

Lifetime – PET is not affected by moisture, mould or mildew and will not rot or deteriorate under normal conditions.

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.